


» XMC401 «



Dual 10 Gigabit Ethernet Switched Mezzanine Card

- » Outstanding Performance & CPU Offload
Intel® Niantic 82599ES 10GbE Controller
- » Flexibility
PCIExpress® x8 Host & SFP+ Ethernet Interface
- » Cost Effective
Highly Integrated Single Chip Solution

XMC401

Dual 10 Gigabit Ethernet Switched Mezzanine Card

Designed for operation in latest high speed networks, the XMC401 provides 2x 10GbE data throughput at full speed.

In addition to the great processing performance on Kontron's CPU side, the next generation 10 Gigabit Switched Mezzanine Card (XMC) provides sufficient data throughput for today's Ethernet networks. Two 10GbE ports attached by PCIe x8 to the host computer, combined with new capabilities and enhancement of the Intel® 82599ES 10 Gigabit Ethernet controller, helps unshackle processors from their predecessor's network

I/O handcuffs and unleashes blazing performance in a variety of usage models. Supporting latest Intel VT technologies, Kontron provides the platform foundation for virtualization and storage over Ethernet usages and provides new opportunities to more efficiently utilize network links. Offering the possibility of either one or two channels as well as the support of copper and/or optical transmission, the XMC401 allows a maximum flexibility. Furthermore, it supports intelligent behaviour through the auto detection feature of copper network configurations.

Technical Information	
Ethernet Controller	Intel® 82599ES (Niantic)
Ethernet Interface	Two 10 Gbit small form factor pluggable (SFP+) interfaces
Host Interface	XMC PCI Express® Gen 2.0 x8 interface
Status LED	8 LEDs for Link activity, Link-up, 1/10 Gb speed
Flash Memory	8 Mbit serial flash device for BOOT ROMs
Serial EEPROM	128kbit serial EEPROM for configuration data 2 kbit serial EEPROM for IPMI FRU data
Power Consumption	7,5 Watt typical
General	According VITA42.0/3/6 IEEE 1386.1-2001 Dimensions : 74 W x 149 D mm, single XMC card Weight : 100gr MTBF: 962421 h MIL-HDBK-217 FN2 Ground Benign 30° 1284865 h Bellcore Issue 6 Ground Benign 30°
Environmental	Operating temp.: 0°C to +55°C Storage temp.: -55°C to +85°C Operating humidity: 93% RH at 40 °C, non-condensing (acc. to IEC 60068-2-78) Operating altitude : 4000 m (13123 ft) above sea level Passive heat sink, forced system air flow
Compliance	Designed to meet or exceed Vibration: DIN/IEC 60068-2-6 Shock: DIN/IEC 60068-2-27 EMC: EN55022 class.B / EN55024 Safety: EN60950-1
Software Support	Linux Windows Server 2003 32/64 Bit Other Drivers on request

Ordering Information		
Article	Part No.	Description
XMC401	1031-3219	Dual 10GbE eXtended Mezzanine Card, SFP+ Cages
KIT-XMC401	1035-5627	Documentation and Windows Driver Software
LIN-BSP-XMC401	1035-5628	Documentation and Linux Driver Software

CORPORATE OFFICES

Europe, Middle East & Africa

Lise-Meitner-Str. 3-5
86156 Augsburg
Germany
Tel.: +49 (0) 821 4086-0
Fax: +49 (0) 821 4086 111
sales@kontron.com

North America

14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: +1 888 294 4558
Fax: +1 858 677 0898
info@us.kontron.com

Asia Pacific

17 Building,Block #1, ABP.
188 Southern West 4th Ring Road
Beijing 100070, P.R.China
Tel.: +86 10 63751188
Fax: +86 10 83682438
info@kontron.cn